

IP54 Enclosed economy soft starter - range 5.5kw to 15 kw

Benefits over Star Delta

- **ELECTRICAL:** To Limit Starting Current Inrush
- **MECHANICAL:** To Reduce Starting Overload Torque
- **APPLICATION:** To Provide Smooth Stepless Acceleration
- **ECONOMIC:** To Save Wear and Tear and Energy



Standard Features

- Interlocked Isolator
- Stop/Start Pushbutton
- Corrosion Resistant Enclosure
- Integral Wall Fixing Brackets

Protection

- Soft Starter With Bypass
- Motor Overload
- Low Voltage Control
- Thyristor Protection

Applications

- Pumps
- Fans
- Conveyors
- Compressors

Technical Data

TQM2KA

	5.5	7.5	11	15
KW rating	5.5	7.5	11	15
Mains power	110-415vAC + or - 10%			
Motor FLC rating (Amps)	11	14	21	28
Dimensions HxWxD (Does not include fixing lugs)	175x280x175		250x350x175	
Weights Kg (approx & unpacked)	5	8	8	8

Note: Due to continuous improvement & development, sizes & specification may change without notice - always check with factory before ordering.

MANUFACTURER

RALSPEED LTD
A1 Hurstwood Court
Mercer Way
Shadsworth Business Park
Blackburn
BB1 2QU

YOUR LOCAL DISTRIBUTOR

IP54 Enclosed digital starter - range 22kw to 90 kw

Benefits over Star Delta

- **ELECTRICAL:** Control Starting Current Inrush
- **MECHANICAL:** To Reduce Starting Overload Torque
- **APPLICATION:** To Provide Smooth Stepless Acceleration
- **ECONOMIC:** To Save Wear and Tear and Energy



Standard Features

- Door interlocked isolator
- Stop start push button
- Local Remote Keyswitch
- 2 Line LCD display & keypad
- Corrosion resistant enclosure
- High quality powder coat finish
- Integral wall fixing lugs
- Large removable gland plate

Protection

- Electronic Overload
- Overload Pre-Alarm
- Too Many Starts Protection
- Phase Fault Detection
- Under-Load Trip
- Electronic "Shearpin"
- Thermistor Input
- Thyristor Fault Protection

Information

- Motor Current
- RMS Volts
- Ambient Temperature
- Time & Date
- Run Hours
- Service Time Indication
- Motor Status
- 1000 Event Datalog

Applications

- Pumps
- Fans
- Compressors
- Chillers
- Rock Crushers
- Mixers

Technical Data

TQM2KD

KW rating	22 / 30	37	45	55	75	90
Mains power	380-415vAC + or - 10%					
Motor FLC rating (Amps)	44 / 60	72	85	105	140	170
Dimensions HxWxD (in mm) <i>(Does not include fixing lugs)</i>	450x300x225	500x400x225			600x400x300	
Weights Kg (approx & unpacked)	15	18	18	18	30	30

Note: Due to continuous improvement & development, sizes & specification may change without notice - always check with factory before ordering.

www.ralspeed.com